




KDS-215GP

Kitchen Display Terminal



KDS-215GP

Kitchen Display Terminal



KDS-215GP

Kitchen Display Terminal



Main Features

- **21.5" All-in-One Terminals** – Purpose-built for kitchen and other demanding industrial environments.
- **Rugged Construction** – Features a robust, tempered-glass display and a fanless system enclosed in a durable metal housing.
- **Industrial-Grade Reliability** – Built with high-quality electronic components to ensure maximum uptime and long-term stability.
- **Sealed Cable Design** – Innovative SR (strain relief) design with female connector plugs allows for easy cable extension while maintaining a secure and sealed connection.
- **Multi-Platform Support** – Compatible with both Android and Linux operating systems.
- **High-Visibility Touch Display** – Bright, clear, and highly responsive touchscreen that functions reliably even with wet fingers or latex gloves.
- **Exceptional Resistance** – Fully resistant to water, grease vapor, and food acids, ideal for high-humidity or food-prep areas.
- **Hygienic Design** – Smooth, seamless surfaces with an edgeless construction make cleaning simple and ensure full hygiene compliance.
- **Optional Software** – Can be equipped with Heng Yu Kitchen Display software for streamlined kitchen operations.
- **Accessory Compatibility** – Supports optional Heng Yu bump bars for enhanced workflow control.

KDS-215GP

Cable outlet method & Waterproof cover design



- KSI Holding, Inc.
- <http://www.ksipos.com>

KDS-215GP Windows System

Features	Model	KDS-215GP-S64	KDS-215GP-SI3	KDS-215GP-SI5
Processor	CPU	Intel® Celeron® Processor J6412	Intel® i3-1115G4	Intel® i5-1135G7
	Frequency	Up to 2.6GHz	Up to 4.1GHz	Up to 4.2GHz
Memory	Technology	Support DDR4 3200MHz, 1*non-ECC SO-DIMM Slot		
	Max. Capacity	Up to 32GB		
Display	Controller	Intel UHD Graphics	Intel UHD Graphics	Intel Iris Xe Graphics
	Graphic Memory	10th Gen Intel® Processors, 800MHz	Up to 48 EUs, 1.25Ghz	Up to 80 EUs,1.3 GHz
	Main Display Resolution	21.5" (1920 x 1080), ratio 16:9		
	Active Area	476.64 x 268.11(mm)		
	Luminance	250cd/m2		
	Viewing Angle (R/ L/ U/ B)	89/ 89/ 89/ 89		
	Touch Panel	PCAP, USB protocol		
Ethernet	Controller	Realtek GBE LAN Chip (RJ45, 10/100/1000 Mbps)		
Storage	Primary	M.2 (NGFF) Key B/B+M Slot (SATA SSD, 2280)	M.2 (NGFF) PCIe4 Key M Slot (NVME SSD, 2280)	
I/O Interface	Main USB	4 x USB-A 3.0		
	Audio	Line-Out/ Mic 3.5mm Jack		
	Serial	DB9 x 1		
	LAN	RJ45 / POE++ LAN (Optional)		
Options	Bumpbar	BB20A / MK15F / USB Speaker		
Power Adaptor	Input	Universal AC 100~240V, 50/60 Hz		
	Output	DC +12V 5A/		
Environment	Storage Temperature	-15°C ~ 55°C		
	Operation Temperature	-0°C ~ 40°C		
	Operation Humidity	10% ~ 85%		
Mounting	Standard	VESA Mount 200 x 200 (mm)		
Dimension	Panel (w/o stand)	530 x 317 x 60 (mm)		

- KSI Holding, Inc.
- <http://www.ksipos.com>

KDS-215GP Android System

Features	Model	KDS-215GP-S35
Processor	CPU	ARM Rockchip RK3568, Quad-core Cortex-A55
	Frequency	Up to 2.0GHz
Primary Storage	SSD	32GB eMMC
Display	Controller	Mali-G52
	Main Display Resolution	21.5" (1920 x 1080), ratio 16:9
	Active Area	476.64 x 268.11(mm)
	Luminance	250cd/m2
	Viewing Angle (R/ L/ U/ B)	89/ 89/ 89/ 89
	Touch Panel	PCAP, USB protocol
Ethernet	Controller	Gigabit Ethernet
I/O Interface	Main USB	USB-A 3.0 x 1, USB-A 2.0 x 3
	Audio	Line-Out 3.5mm Jack (Optional)
	Serial	DB9 x 1
	LAN	RJ45 x 2 / POE++ LAN (Optional)
Options	Bumpbar	BB20A / MK15F / USB Speaker
Power Adaptor	Input	Universal AC 100~240V, 50/60 Hz
	Output	DC +12V 5A/ Support POE++ power (Optional)
Environment	Storage Temperature	-15°C ~ 55°C
	Operation Temperature	-0°C ~ 40°C
	Operation Humidity	10% ~ 85%
Mounting	Standard	VESA Mount 200 x 200 (mm)
Dimension	Panel (w/o stand)	530 x 317 x 60 (mm)

- KSI Holding, Inc.
- <http://www.ksipos.com>